

Lowrance HDS-12 Gen-2 Touch Combo

Overview

Display	Widescreen, 16:9; WXGA TFT LCD
Resolution	1280 x 800
Power Output: RMS (PTP)	Max 500W RMS
Operating Frequency	(50/200 or 83/ 200 kHz) + 455/800 kHz
Media Port	2 SD (full size)
Warranty	Two Year

Display

Display Resolution	1280 x 800
Display Type	WXGA TFT LCD
GPS and Sonar Overlay Data	Yes
Split Screen Presentation	Max of 4
Display Size	12.1" / 307 mm
Brightness	1250 nits

Sonar

Depth Alarm	Yes
EchoSounder Frequencies	(50/200 or 83/ 200 kHz) + 455/800 kHz
Shallow Alarm	Yes
Standard Fishfinding Features: colourLINE™ or GRAYLINE®, ASP™, FishSymbol I.D.™, FishTrack™, and more	Yes
Transducer Type	(50/200 or 83/ 200 kHz) + 455/800 kHz

Technical/Environmental

Operating Temperature	-15° C to + 55° C (+ 5° F to + 131° F)
Casing	8.83" H x 12.91" W x 3.75" D (224 x 328 x 95 mm)
Product Width	12.91"
Product Depth	3.75"
Product Height	8.83"

Power

Power Consumption	26 W (2.0 A @ 13 V DC)
Power Supply (Supply Voltage)	12 V DC (10.8 - 17.0 V DC min - max)

Communications

NMEA Input	Micro-C (1)
------------	-------------

GPS Navigation

Navigation: Routes	200
Navigation: Waypoint Storage	5000
GPS Antenna Type	Internal, high-sensitivity GPS+WAAS (Americas) or GPS+EGNOS+MSAS (non-Americas)
GPS Alarms	Yes
Background Mapping	Built-in Insight USA™ (Americas) or Worldwide background map (non-Americas)

Other

Languages	36 total, available on 5 Language Packs
-----------	---